

## **Devonshire®**

Undermount Bathroom Sink K-2336

#### **Features**

- Oval basin.
- Overflow drain.
- No faucet holes; requires wall- or counter-mount faucet.
- Coordinates with other products in the Devonshire collection.

#### Material

Vitreous china.

#### Installation

Under-mount.

#### **Recommended Products/Accessories**

K-9018 P-Trap

### **Included Components**

Additional Components: 1193643 Basin clamps



ADA CSA B651

#### Codes/Standards

ASME A112.19.2/CSA B45.1 ADA ICC/ANSI A117.1 CSA B651

### **KOHLER® One-Year Limited Warranty**

See website for detailed warranty information.

#### **Available Colors/Finishes**

Color tiles intended for reference only.


| Color | Code | Description   |
|-------|------|---------------|
|       | 0    | White         |
|       | 96   | Biscuit       |
|       | 47   | Almond        |
|       | NY   | Dune          |
|       | 95   | Ice™ Grey     |
|       | G9   | Sandbar       |
|       | K4   | Cashmere      |
|       | 58   | Thunder™ Grey |
| 413   | 7    | Black Black™  |



# **KOHLER**®


## **Devonshire®**

# Undermount Bathroom Sink K-2336



Recommended ADA Installation





## € of Fitting 2-1/2" (64 mm) 8-3/16" (208 mm) 16-1/2" 5-11/16" (144 mm) (419 mm) 1-3/16" (30 mm) -20-1/2" (521 mm)-1/2" (13 mm) 8-5/8" (219 mm) 14-1/4" (362 mm) 14-3/8" (102 mm) (365 mm) 3/8" Hot 3/8" Cold 1-1/4" Outlet Standard Installation

### **Technical Information**

All product dimensions are nominal.

Bowl configuration: Single

Installation: Under-mount

Bowl area (Only): Length: 18-1/8" (460 mm)

Width: 14" (356 mm)

Water depth: 4-3/16" (106 mm)

Drain hole: 1-3/4" (44 mm)

Template: 1050263-7, required, not included

#### **Notes**

Install this product according to the installation instructions.

NOTICE: Countertop manufacturer or cutter must use the current product template available at www.kohler.com, or by calling 1-800-4KOHLER. Kohler Co. is not responsible for cutout errors when the incorrect cutout template is used. ADA, CSA B651 compliant when installed to the specific requirements of these regulations.

